Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 200539

EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-556-001 REV: 1.2

0.56" Dual Digit Displays

MODEL NO : ELD-556YWA ECN : Page: 1/5

Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

Applications:

- Audio equipment
- Instrument panels
- Digital read out display

Descriptions :

- The ELD-556 series is a large 14.2mm (0.56")high seven segment display design for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These device is made with white segments and gray surface.

PART NO	CHIP		C.C. or C.A.
	Material	Emitted Color	
ELD-556YWA	GaAsP/GaP	Yellow	C.A.

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.
TEL : 886-2-2267-2000,2267-9936
FAX : 886-2-2267-6244,22676189,22676306
http://www.everlight.com

0.56" Dual Digit Displays

MODEL NO : ELD-556YWA ECN : Page: 2/5

■ Package Dimensions:



■ NOTES:

1.All dimensions are in millimeters , tolerance is 0.25mm unless otherwise noted.

2.Above specification may be changed without notice.
Supplier will reserve authority on material change for above specification.

EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-556-001 REV: 1.2

0.56" Dual Digit Displays

MODEL NO : ELD-556YWA ECN : Page: 3/5

■ Absolute maximum ratings at Ta = 25℃ :

Parameter	Symbol	Rating	Unit
Reverse Voltage	Vr	5	V
Forward Current	If	25	mA
Operating Temperature	Topr	-40 to +85	℃
Storage Temperature	Tstg	-40 to +100	℃
Soldering Temperature	Tsol	260 ± 5	℃
Power Dissipation	Pd	85	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	160	mA

■ Electronic optical characteristics :

Parameter		Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous Intensity	Pre segment	Iv	1.05	1.9	----	mcd	If=10mA
	Pre decimal point		0.28	0.56	----	mcd	If=10mA
Peak Wavelength		λ p	----	585	----	nm	If=20mA
Dominant Wavelength		λ d	----	590	----	nm	If=20mA
Spectrum Rediation Bandwidth		△λ	----	35	----	nm	If=20mA
Forward Voltage		Vf	1.7	2.0	2.4	V	If=20mA
Reverse Current		Ir	----	----	10	μA	Vr=5V

EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-556-001 REV: 1.2

0.56" Dual Digit Displays

MODEL NO : ELD-556YWA ECN : Page: 4/5

■ Reliability test item and condition:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260℃ ± 5 ℃	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85℃ 30min ∫ 5 min L : -55℃ 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100℃ 5min ∫ 10 sec L : -10℃ 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100℃	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55℃	1000 HRS	76 PCS	0/1
6	DC Operating Life	If = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85℃/85% RH	1000 HRS	76 PCS	0/1

0.56" Dual Digit Displays

MODEL NO: ELD-556YWA ECN : Page: 5/5

Typical Electro-Optical Characteristic Curves: